

## Z-6182

### Advanced Dual-Laser Omidirectional Scanner

The Z-6182 is a compact vertical scanner empowered with the unique dual-laser technology, enabling 40 scan lines at a rate of 3,600 scans per second. Along with ZEBEX proprietary Z-SCAN+ hardware decoding technology, the Z-6182 guarantees unbeatable decoding speed and accuracy, the best choice for high-traffic applications, including hypermarket, healthcare, warehouse management and manufacturing process control.

- Aggressive scanning performance
- Instant "object-fly-by" at first-read-success scan
- Large scan field
- Barcode stitching capable
- Built-in EAS antenna and expandability for a RFID reader
- Easy on-site configuration and upgradeability



#### OPERATIONAL

Light Source	Dual 650 nm visible laser diodes (VLD)
Depth of Field	5 mil: 0 – 60 mm
	7.5 mil: 0 – 150 mm
	10 mil: 0 – 190 mm
	13 mil: 0 – 240 mm
	20 mil: 0 – 320 mm
Scan Pattern	10 directions of scan field
Scan Rate	3,600 scans per second
Scan Line	40
Print Contrast	30% @ UPC/EAN 100%
Indicator	Two-color LED (blue, red)
Beeper Operation	Programmable tone & volume
System Interface	Keyboard, RS-232, HID USB, USB Virtual COM, OPOS, JPOS

#### PHYSICAL

Dimension	152.0 × 152.0 × 88.0 mm
Weight	685 g (without cable)
Cable	Standard 2M straight

#### POWER

Input Voltage	9 VDC ±10%
Power Consumption	4.05 watts
Operating Current	450 mA typical

#### REGULATORY

Laser Class	CDRH Class IIa; IEC 60825 Class 1
EMC	CE EN55022 B, FCC Part 15 Class B, VCCI, BSMI

#### ENVIRONMENTAL

Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	5% – 90% RH (no dewing allowed)
Light Level	Up to 4,000 Lux (fluorescence)
Drop Durability	Designed to withstand 1M drops
Compatibility	EAS compatible

#### DECODING CAPABILITY

1D Barcode	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF 2 of 5, IATA Code, MSI, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, JAP, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded
------------	--



1. LED touch-sensing buttons for tone & volume adjustment
2. EAS compatible & multi-interface support
3. Optional mounting dock
4. Optional top cover

