

# POS-5700

## Robust Touch Screen Workstation

POS-5700 series is a fully integrated TFT/LCD Touch Screen Workstation that offers best price-performance value for our global POS expert customers. It provides countless features with low power design, high performing Atom processor, and integrated chipset that supports dual monitor output.

POS-5700 differentiates itself through its superb internal housing design, which vastly improves noise reduction, heat dissipation and also makes the POS hardware maintenance a lot easier vs. the older models. The special featured aluminum die-casting base and the securely mounted monitor also provide stability and reliability during the touch screen operations.

POS-5700 offers various hardware customizations upon OEM requests, including VESA Wall-Mount models, choices of rear mount between customer pole display and 2nd LCD display, and etc... This Point of Sale system is compatible with both Linux and Windows Operating Systems, and is able to integrate with a wide selection of retail devices. It ensures competitiveness of your business and maximizes return on your investments.

### Feature



Easy Tilting-Angle Adjustment



Wide variety of optional peripherals (MSR, Customer Display...etc)



Atom  
1.6 GHz

17/15/12.1"  
Display  
(Touch)

Low-Noise  
System

USB  
Giga LAN  
RS-232

Water-Spill  
Proof

Internal  
Adapter

- Low power design Intel Atom processor (1.6GHz, 533MHz)
- Compact and solid industrial design
- Low noise system with reliable thermolysis
- Wide range tilting angle 15 ~ 80 degrees
- Left-sided PS/2, USB for friendly installation
- Optional Peripherals available:  
MSR/Customer Display/2nd VGA Display
- Rear panel ventilators with water spill proof  
Front panel with water spill proof
- Internal power adapter hidden on base
- Cost effective and space-saving

# POS-5700 Robust Touch Screen Workstation

## Specification

Model	POS-5717-AT	POS-5715-AT	POS-5712-AT
<b>Main Board</b>			
CPU	Intel Atom N270 (1.6GHz , 512KB Cache, 533MHz FSB)		
Chipset	Intel 82945GSE + 82801GBM (ICH7)		
System Memory	200-pin SODIMM, DDR266/333, 256MB/512MB/1GB		
Graphic Memory	Share System Memory 64~224MB		
OS Support	POS Ready 2009, POS Ready 7, Linux, Windows XP Pro, Vista, Windows 7		
<b>Display</b>			
Screen Size	17"	15"	12.1"
Brightness	300 nits	250 nits	400 nits
Resolution	1280x1024 Pixel	1024 x 768 Pixel	1024 x 768 Pixel
Touch Screen	5 Wire Resistive Type or SAW		
Tilting Angle	15°~80°		
<b>Storage</b>			
HDD	1 x 2.5" SATA		
Compact Flash	1x Slot Type II, Non-removable		
<b>I/O Ports</b>			
Serial	2 x COM with Power Selected 5/12V, 1 x COM without Power Output		
Parallel	1 x Parallel Port		
USB	6 x USB2.0 (External), 2 x USB2.0 (Internal, 1 for Touch BD)		
PS/2 Mouse	1 x 6-pin Mini DIN		
PS/2 Key Board	1 x 6-pin Mini DIN		
LAN	1 x RJ-45, Giga LAN Support		
VGA	1 x DB-15, Female		
DC Out	1 x 12VDC Jack for Customer Display		
Cash Drawer	1 x RJ-11, 12/24 VDC Selectable		
Audio Jack	1 x Audio Out with Internal Speaker 2W x 2		
<b>Others</b>			
Power Input	External Adapter 12VDC 90W,4-pin Connector with Lock		
Color	Black, Silver		
Compliance	FCC / CE / WEEE / RoHS		
Weight	7 Kg	6.5 Kg	6 Kg
Dimension (W x D x H:mm)	415 x 320 x 410	367 x 320 x 360	345 x 320 x 340
Operating Temperature	5°C~40°C		
Storage Temperature	-20°C~ 60°C		
Storage Humidity	20% - 80% RH, non-condensing		

## Optional Peripherals



PRP-088 Receipt Printer



Durable Cash Drawers



Secondary Display

ISO-9002 Certified



Beyond Mere POS

<http://www.fametech.com.tw>
**TYSSO**®