

Honeywell Fusion 3780 (MK3780-71A38)

USB, 4842 Lux, Omnidirectional, 1D, stand, coiled low speed USB cable



Price details:

Price excl. VAT: 219.69 €

Eco fees: 0.00 €

VAT 21 %: 46.13 €

Product details:

Product code: MK3780-71A38

EAN: 4054318749454

Manufacturer: Honeywell

265.82 €

* VAT included

PDF generated on: 16 January, 2016

Honeywell's Fusion 3780 is an affordable hand-held omnidirectional laser scanner with single-line capability that increases retail checkout system efficiency with its automatic in-stand operation, optionally integrated EAS, and industry-leading scan performance.

Fusion combines omnidirectional and single-line laser bar code scanning into a lightweight, ergonomic hand-held form factor. The 20-line scan pattern provides superior scanning over existing single-line hand-held scanners making Fusion ideal for medium-volume retailers including specialty stores, pharmacies, liquor stores, and convenience stores.

An adjustable stand with 50° of tilt and three locking positions provides flexibility for the user to position the scanner for individual comfort and optimal performance. Stabilized with a weighted metal base, the stand may also be hard-mounted to counter or walls.

Fusion also includes Code Gate, a Honeywell patented feature used in the highly successful Voyager series. An integrated infra-red (IR) sensor automatically activates the laser when a bar code is present. The user then properly aligns the bar code before pressing the button, transmitting the data to the host. This feature provides the ability to pass over other bar codes, selecting only the required code. No other scanner offers this much control.

Standard features such as Flash ROM, MetroSelect and MetroSet 2 programming, and user replaceable cables protect your investment by enabling Fusion to grow with you and your application requirements.

Main specifications:

Scanning

Sensor type:	Laser
Scan type:	1D
Linear (1D) barcodes supported:	GS1-128 (UCC/EAN-128)
2D (matrix & stacked) barcodes supported:	N
Pitch reading angle:	-60 - 60 °

Ports & interfaces

Connectivity technology:	Wired
Interface:	USB

Design

Colour of product:	Grey
Type:	Handheld

Power

Power consumption (typical):	1.4 W
Power consumption (standby):	1 W
Input voltage:	5 V

Operational conditions

Operating temperature (T-T):	-20 - 40 °C
Storage temperature (T-T):	-40 - 60 °C
Light levels (direct sunlight):	0 - 4842 lx

Weight & dimensions

Width:	65 mm
Depth:	189 mm
Height:	73 mm
Weight:	195 g

Packaging content	
Cables included:	USB

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.